

BikeYoke compatibility chart - Specialized Enduro

Bike model	BikeYoke model							
	#1	#2.1	#3	#4	#5	#6	#6.1	#7
Enduro 2010 26"	200x51*							
Enduro 2010 EVO 26"	200x51*							
Enduro 2011 26"	200x51*							
Enduro EVO 2011 26"	200x51*							
Enduro 2012 26"	200x51*							
Enduro EVO 2012 26"	200x51*							
Enduro 2013 26"		216x63						
Enduro EVO 2013 26"					216x63			
Enduro 2013 29"			200x57		210x55**			
Enduro 2014 26"			200x57		210x55**			
Enduro EVO 2014 26"					216x63			
Enduro 2014 29"			200x57		210x55**			
Enduro 2015 650b		210x55*		200x57				
Enduro EVO 2015 650b		216x63						
Enduro 2015 29"			200x57		210x55**			
Enduro 2016 650b		210x55**		200x57				
Enduro EVO 2016 650b		216x63						
Enduro 2016 29"			200x57		210x55**			
Enduro 2017 650b						200x57	200x57	210x55**
Enduro 2017 29 / 6Fatty						200x57	200x57	210x55**
Enduro 2018 650b						200x57	200x57	210x55**
Enduro 2018 29 / 6Fatty						200x57	200x57	210x55**
Enduro 2019 650b						200x57	200x57	210x55**
Enduro 2019 29 / 6Fatty						200x57	200x57	210x55**

ANNOTATIONS

shock size in mm	equivalent in inch
200x51	7.875x2.0
200x57	7.875x2.25
216x63	8.5x2.5
210x55	-

All allowed combinations will create same geometry and travel as original, unless specified differently

Yoke #6 = high setting geometry
 Yoke #6.1 = low geometry setting
 Yoke #7 = low geometry setting

*rear wheel travel will be reduced by ~8mm

** rear wheel travel will be reduced by ~4mm

Standard shocks must have standard 12.7mm (1/2") diameter bushings and maximum 12.70mm eyelet width

Due to the numerously available shocks, please carefully check for sufficient clearance between tires, shock and frame parts in any position throughout the complete shock stroke, especially when bottoming out - frame or shocks parts must not collide in any position!