

OIL & PRESSURE SPECS



OIL VOLUMES BIKEYOKE DROPPERS		volume	tolerance
REVIVE / REVIVE MAX 125		36 ml	+/- 2 ml
REVIVE / REVIVE MAX 160	pressure (psi):	42 ml	+/- 2 ml
REVIVE / REVIVE MAX 185	min. standard max. 210 ——— 250 ——— 290	46 ml	+/- 2 ml
REVIVE / REVIVE MAX 213		55 ml	+/- 2 ml
DIVINE 125	pressure (psi):	46 ml	+/- 2 ml
DIVINE 160	min. standard max. 250 ——— 300 ——— 350	52 ml	+/- 2 ml
DIVINE 185		58 ml	+/- 2 ml
DIVINE SL RASCAL 80		13 ml	+ 2 ml
DIVINE SL 80	pressure (psi):	13 ml	+ 2 ml
DIVINE SL 100	min. standard max. 250 ——— 300 ——— 350	13 ml	+ 2 ml
DIVINE SL 125		13 ml	+ 2 ml

OIL SPEC BIKEYOKE DROPPERS

ex works:
 96% MOBIL DTE 10 EXCEL 15 (viscosity: 16 cSt @ 40°C)
 4% R.S.P. No Stick Slip

Suspension oils for bicycle components from other manufacturers with similar viscosity can usually be used, however, experience has shown that our seatposts work best with the oil mix described above.

LOWER TUBE GREASE BIKEYOKE DROPPERS

ex works: R.S.P. Slick Kick

alternatives:
 R.S.P. Soft Grease
 Rock Shox Butter
 KS Post Paste
 Buzzy's Slick Honey